

# Signal light tower, Series 46, Raised, IP44

46-581.1800



<https://www.eao.com/p/a0ee064b>

Your product:

---



## 46-581.1800

### Signal light tower, Series 46, Raised, IP44

#### PRODUCT RANGE

**HMI function:** Indicator

**Series:** Series 46

#### FRONT

**Front form:** Round

**Colour:** Grey

#### MOUNTING

**Design:** Raised

**Mounting type:** Panel mounting

#### MECHANICAL CHARACTERISTICS

**Total weight:** 0.165 kg

#### AMBIENT CONDITION

**IP front protection:** IP44

**Operating temperature:** - 25 °C ... + 65 °C

#### OTHER

**Material:** Plastic

**Colour RAL:** 7016 RAL

Your product consists of the following **1 COMPONENTS:**

---



## 46-581.1800 Connection module

### FRONT

**Front form:** Round

**Colour:** Grey

### MOUNTING

**Mounting type:** Panel mounting

### ELECTRICAL CHARACTERISTICS

**Rated insulation voltage  $U_i$ :**  $U_i$  690V -  $U_{imp}$  4KV (IEC-EN60947-1)

**Pollution degree:** 3

**Protection class:** II, according to EN / IEC 61140

### MECHANICAL CHARACTERISTICS

**Weight:** 0.165 kg

### AMBIENT CONDITION

**IP front protection:** IP44

**IK front protection:** IK07

**Operating temperature:** - 25 °C ... + 65 °C

### CERTIFICATE

**Conformities:** CE

**REACH:** REACH compliant

**RoHS:** RoHS compliant  
**Standards:** IEC EN 60947-1, IEC EN 60947-5-1

**OTHER**

**Short Description:** Connection module, Round, IP44, IK07  
**Material:** Plastic  
**Colour RAL:** 7016 RAL