Switches are supplied without UL, cULus & CSA marking unless specified.

Specific models & ratings noted on General Specifications page.

TYPICAL SWITCH ORDERING EXAMPLE S1 3 M20 Poles **Small Toggles Small Bushings** Contact Materials & Ratings SPST S .413" (10.5mm) Bat **S**1 .350" (8.9mm) Threaded with Keyway Silver; Rated SPDT 6A @ 125V AC & 3A @ 250V AC **S2** .200" (5.08mm) Bat 6mm .350" (8.9mm) Threaded with **S4** Keyway DPST Gold: Rated **S3** .256" (6.5mm) Bat 0.4VA max @ 28V AC/DC max DPDT **S2** .350" (8.9mm) Smooth with Keyway Ε .450" (11.4mm) Flatted SP3T Gold over Silver; Rated A1 .280" (7.1mm) Threaded with Keyway * E2 .256" (6.5mm) Flatted 3PDT 6A @ 125V AC & 0.4VA max @ 3 A2 .280" (7.1 mm) Smooth with Keyway 28V AC/DC max **E4** .840" (21.3mm) Flatted 4PDT D1 .350" (8.9mm) Threaded with D Flat DP3T * Q .550" (14.0mm) Cone 6mm .350" (8.9mm) Threaded with * Q2 .640" (16.26mm) Cone D4 * Q4 .840" (21.3mm) Cone .350" (8.9mm) Threaded Splashproof * C .571" (14.5mm) Color Tipped Cone with D Flat (combines only with S, S2 & S3) D .840" (21.3mm) Color Capped Cone Terminals Specify cap color for toggles C & D 6mm .350" (8.9mm) Threaded Splash-01 Solder Lug* proof with D Flat (combines only with at the end of the part number. *Available on 1- and 2-pole only. S, S2 & S3) 02 Quick Connect Circuits .250" (6.35mm) Straight PC *1 ON NONE OFF .425" (10.8mm) Wirewrap 2 ON NONE ON 06 .750" (19.05mm) Wirewrap Large Toggles Large Bushings 3 ON OFF ON 07 .964" (24.5mm) Wirewrap В .453" (11.5mm) Large Bat Large .472" (12mm) Threaded 5 ON NONE (ON) with Keyway 1.062" (27.0mm) Wirewrap **B2** .689" (17.5mm) Large Bat 8 (ON) OFF (ON) Large .472" (12mm) Threaded R .610" (15.5mm) Large Flatted Splashproof with D Flat 9 ON OFF (ON) * Wire harness & cable assemblies **4 ON ON ON offered only in Americas **6 (ON) ON (ON) **7 Locking Lever **Bushings For Locking Levers** ON ON (ON) .201" (5.1mm) Dia. Locking Lever .291" (7.4mm) Threaded with Keyway DESCRIPTION FOR TYPICAL ORDERING EXAMPLE () = Momentary LI for Lever Lock * ON-NONE-OFF circuit avail-M2013SS1W01 6mm .291" (7.4mm) Threaded with able in 1- and 2-pole only. L4 Keyway for Lever Lock ** 3-ON circuits Smooth with Keyway for Lever Lock .413" (10.5mm) Bat Toggle .295" (7.5mm) Threaded Splashproof L3 with D Flat for Lever Lock 1/4-40 .350" (8.9mm) 6mm .295" (7.5mm) Threaded Splash-Threaded Bushing with Keyway proof with D Flat for Lever Lock SPDT IMPORTANT: Silver Contacts ON-OFF-ON Circuit with 6-Amp Rating

Solder Lug Terminals