

# Pendant control, Series 46, Raised

46-457.1418



<https://www.eao.com/p/f65b54ad>

Your product:

---



## 46-457.1418 Pendant control, Series 46, Raised

### PRODUCT RANGE

<b>HMI function:</b>	Housing
<b>Series:</b>	Series 46

### FRONT

<b>Colour:</b>	Yellow
----------------	--------

### MOUNTING

<b>Design:</b>	Raised
<b>Mounting cut-out:</b>	Ø 22 mm
<b>Mounting type:</b>	Panel mounting

### MECHANICAL CHARACTERISTICS

<b>Tightening torque:</b>	0.8 ... 1.2 Nm (7.1÷10.6 Lb-in)
<b>Total weight:</b>	0.4 kg

### AMBIENT CONDITION

<b>IP front protection:</b>	IP65, IP66
<b>Operating temperature:</b>	- 35 °C ... + 80 °C

### OTHER

<b>Number of holes:</b>	3 (2+1)
<b>Housing material:</b>	Plastic

**Product attributes:**

Suitable for outdoor applications

Your product consists of the following **1 COMPONENTS:**

## 46-457.1418 Pendant control

**FRONT****Colour:** Yellow**MOUNTING****Mounting cut-out:** Ø 22 mm**Mounting type:** Panel mounting**ELECTRICAL CHARACTERISTICS****Rated insulation voltage  $U_i$ :**  $U_i$  300V -  $U_{imp}$  2.5KV (IEC-EN60947-1)**Pollution degree:** 3**Protection class:** II, according to EN / IEC 61140**MECHANICAL CHARACTERISTICS****Tightening torque:** 0.8 ... 1.2 Nm (7.1÷10.6 Lb-in)**Weight:** 0.4 kg**AMBIENT CONDITION****IP front protection:** IP65, IP66**IK front protection:** IK08**Operating temperature:** - 35 °C ... + 80 °C

## CERTIFICATE

<b>Approbations:</b>	CSA, UL
<b>Conformities:</b>	CE
<b>REACH:</b>	REACH compliant
<b>RoHS:</b>	RoHS compliant
<b>Standards:</b>	CSA C22-2, IEC EN 60204-1, IEC EN 60947-1, IEC EN 60947-5-1, UL508

## OTHER

<b>Short Description:</b>	Pendant control
<b>Number of holes:</b>	3 (2+1)
<b>Dimension:</b>	83 mm x 197 mm
<b>Housing material:</b>	Plastic
<b>Product attributes:</b>	Suitable for outdoor applications
<b>Dimension drawings:</b>	

